Google™
Groups ⊙ BETA

gawk gen-po | Search Groups | Advanced Groups Search
Preferences

| Members: | Sign in |
| New users: | Join |

Google Groups

Create a new group

Recently visited [clear]

comp.lang.awk

About Google Groups

Searched all groups   Results **1 - 10** of 11 for **gawk gen-po**. **(0.03** seconds)

Sort by relevance   **Sorted by date**

unofficial patch for gawk to add -Wexec / --exec
... its way into 3.1.5. Arnold ----- cut here ----- **gawk**-3.1.
4 ... exec=file\n"), fp); fputs(_("\tW **gen-po**\t\t ...
comp.lang.awk - Sep 20 2004, 1:20 pm by Aharon Robbins - 4 messages - 4 authors

Strange gawk CGI issue
... **gen-po**? Do these work too? I didn't try those, but they would cause failure also.
I'd guess that apache somehow adds the CGI arguments to command line and **gawk** ...
comp.lang.awk - Sep 14 2004, 1:06 pm by Ted Davis - 13 messages - 5 authors

Çë½ÏÂÃæÕâ¸öÖ¸ÁÔõÃ´»ØÊÂ£¿
... copyright -W dump-variables[=file] --dump-variables[=file] -W **gen-po** --**gen-po** -W
help ... W version --version To report bugs, see node `Bugs' in `**gawk**.info', which ...
cn.bbs.comp.linux - Mar 24 2004, 6:58 am by ÇÚÓÐ¹¦æÒÎÞÒß - 1 message - 1 author

but I want the GNU versions of packages
... W dump-variables[=fichier] --dump-variables[=fichier] -W **gen-po** --**gen-po** -W help ...
rapporter une anomalie, voir la rubrique « Bugs » dans « **gawk**.info » dans ...
linux.debian.devel - Jul 21 2003, 7:51 pm by Mathieu Roy - 36 messages - 21 authors

CVS commit: pkgsrc
... New `--**gen-po**' option creates GNU gettext .po files for strings marked with a leading
underscore. - **Gawk** now completely interprets special file names ...
fa.netbsd.source-changes - Apr 4 2002, 5:59 am by Stoned Elipot - 7 messages - 6
authors

gawk 3.1.0 released
... 3. New `--**gen-po**' option creates GNU gettext .po files for strings marked with a
leading underscore. 4. **Gawk** now completely interprets special file names ...
gnu.utils.bug - Jun 6 2001, 1:33 am by Aharon Robbins - 1 message - 1 author

Second beta of gawk 3.1 now available
... 3. New `--**gen-po**' option creates GNU gettext .po files for strings marked with a
leading underscore. 4. **Gawk** now completely interprets special file names ...
comp.lang.awk - May 14 2001, 10:02 am by Arnold D. Robbins - 9 messages - 6 authors

gawk 3.0.95, beta for gawk 3.1.0, now available
... 3. New `--**gen-po**' option creates GNU gettext .po files for strings marked with a
leading underscore. 4. **Gawk** now completely interprets special file names ...
comp.lang.awk - Feb 26 2001, 12:48 am by Arnold D. Robbins - 2 messages - 2 authors

gawk 3.0.95, beta release for gawk 3.1.0, now available
... 3. New `--**gen-po**' option creates GNU gettext .po files for strings marked with a
leading underscore. 4. **Gawk** now completely interprets special file names ...
gnu.utils.bug - Feb 26 2001, 12:44 am by Aharon Robbins - 1 message - 1 author

Gawk 3.1 new feature list
... 3. New `--**gen-po**' option creates GNU gettext .po files for strings marked with a ...
5. **Gawk** now completely interprets special file names internally, ignoring the ...
comp.lang.awk - Sep 3 2000, 5:58 am by Arnold D. Robbins - 13 messages - 5 authors

Google™

gawk gen-po | Search | Advanced Search
Preferences

Web

Results **1 - 10** of about **411** for gawk gen-po. (0.06 seconds)

Did you mean: gawk *genpo*

Effective awk Programming, 3rd Edition: Chapter 9 ...
... Run **gawk --gen-po** to create the .po file:. $ **gawk --gen-po** -f guide.awk >
guide.po. This produces:. #: guide.awk:4 msgid "Don't Panic" msgstr ...
www.oreilly.com/catalog/awkprog3/chapter/ch09.html - 33k - Cached - Similar pages

The GNU Awk User's Guide: Internationalization
... **gawk --gen-po** -f guide.awk > guide.po. When run with `**--gen-po'** , **gawk** does
not execute your program. Instead, it parses it as usual and prints all ...
www.sunsite.ualberta.ca/Documentation/ Gnu/**gawk**-3.1.0/html_chapter/**gawk**_11.html - 39k - Cached - Similar pages

The GNU Awk User's Guide - Internationalization with gawk
... When run with @option{**--gen-po**}, @command{**gawk**} does not execute your program.
... will be taught to automatically run `**gawk --gen-po'** for `.awk' files, ...
www.linuxselfhelp.com/ gnu/**gawk**/html_chapter/**gawk**_11.html - 30k - Cached - Similar pages

I18N Example - The GNU Awk User's Guide
... Run ` **gawk --gen-po** ' to create the .po file: $ **gawk --gen-po** -f guide.awk >
guide.po. This produces: #: guide.awk:4 msgid "Don't Panic" msgstr ...
www.gnu.org/software/**gawk**/ manual/html_node/I18N-Example.html - 8k - Cached - Similar pages

The GNU Awk User's Guide
www.delorie.com/gnu/docs/**gawk**/gawk_155.html, search ... Run `**gawk --gen-po'** to
create the `.po' file:. $ **gawk --gen-po** -f guide.awk > guide.po ...
www.delorie.com/gnu/docs/**gawk**/**gawk**_155.html - 8k - Cached - Similar pages

gawk - Linux Command - Unix Command
... Run **gawk --gen-po** -f myprog.awk > myprog.po to generate a .po file for your
program. 5. Provide appropriate translations, and build and install a ...
linux.about.com/library/cmd/blcmdl1_**gawk**.htm - 101k - Cached - Similar pages

The GNU Awk User's Guide - I18N Example
... Run `**gawk --gen-po'** to create the `.po' file: $ **gawk --gen-po** -f guide.awk >
guide.po. This produces: #: guide.awk:4 msgid "Don't Panic" msgstr ...
kansai.anesth.or.jp/gijutu/awk/**gawk**/**gawk**_155.html - 4k - Cached - Similar pages

gawk - pattern scanning and processing language
... Run **gawk --gen-po** -f myprog.awk > myprog.po to gener- ate a .po file for your
program. 5. Provide appropriate translations, and build and install a ...
www.awk-scripting.de/cgi/ wiki.cgi/scripting/manpage.html - 79k - Cached - Similar pages

The GNU Awk User's Guide
... Run **gawk --gen-po** to create the .po file: $ **gawk --gen-po** -f guide.awk > guide.po.
This produces: #: guide.awk:4 msgid "Don't Panic" msgstr ...
ftp.azc.uam.mx/mirrors/gnu/Manuals/ **gawk**-3.1.1/html_node/I18N-Example.html - 5k - Cached - Similar pages

linux manual page - gawk(1)
... Run "**gawk --gen-po** -f myprog.awk > myprog.po" to generate a .po file for your
program. 5. Provide appropriate translations, and build and install a ...
linux.com.hk/PenguinWeb/ manpage.jsp?section=1&name=**gawk** - 121k - Cached - Similar pages